

무대 상부 기계 배치 순서 및 자원

순번	구분	동력	속도(MIN)	허용하중(Kg)	구동방식	간격(mm)		비고
1	Placard Batten	2.2Kw × 4P	12M	400	WINCH TYPE	+500	+2,150	
2	Apron Light Batten	3.75Kw × 4P	12M	500	WINCH TYPE	+1,650	+1,650	
3	Proscenium Board	5.5Kw × 6P	6M	1,800(Total)	WINCH TYPE	0	0	
4	Main Draw Curtain	15Kw × 4P	0~60M	700(Total)	WINCH TYPE	-500	-500	
		0.75Kw × 4P	24M		TRACTION TYPE			
5	SUS Light Batten No.1	3.75Kw × 4P	12M	800	WINCH TYPE	-500	-1,000	
6	Set Batten No.1	15Kw × 4P	0~60M	800	WINCH TYPE	-800	-1,800	
7	Set Batten No.2	15Kw × 4P	0~60M	800	WINCH TYPE	-400	-2,200	반사판
8	Draw Curtain No.1	3.75Kw × 4P	12M	700	WINCH TYPE	-350	-2,550	
		0.75Kw × 4P	24M		WINCH TYPE			
9	SUS Light Batten No.2	3.75Kw × 4P	12M	800	WINCH TYPE	-625	-3,175	
10	Roll Screen Batten	3.75Kw × 4P	12M	800	WINCH TYPE	-350	-3,525	
	Roll Screen	450w × 4P	6M		Motor Drive Lifting Method			
11	Set Batten No.3	15Kw × 4P	0~60M	800	WINCH TYPE	-625	-4,150	반사판
12	Draw Curtain No.2	3.75Kw × 4P	12M	700	WINCH TYPE	-325	-4,475	
		0.75Kw × 4P	24M		WINCH TYPE			
13	Front Screen	3.75Kw × 4P	18M	800(Total)	WINCH TYPE	-300	-4,775	
14	SUS Light Batten No.3	3.75Kw × 4P	12M	800	WINCH TYPE	-350	-5,125	
15	Set Batten No.4	15Kw × 4P	0~60M	800	WINCH TYPE	-350	-5,475	
16	Set Batten No.5	15Kw × 4P	0~60M	800	WINCH TYPE	-625	-6,100	반사판
17	Draw Curtain No.3	3.75Kw × 4P	12M	700	WINCH TYPE	-400	-6,500	
		0.75Kw × 4P	24M		WINCH TYPE			
18	SUS Light Batten No.4	3.75Kw × 4P	12M	800	WINCH TYPE	-575	-7,075	
19	Set Batten No.6	15Kw × 4P	0~60M	800	WINCH TYPE	-400	-7,475	
20	Set Batten No.7	15Kw × 4P	0~60M	800	WINCH TYPE	-575	-8,050	반사판
21	Upper Horizont Light Batten	3.75Kw × 4P	12M	900	WINCH TYPE	-300	-8,350	
22	Set Batten No.8	15Kw × 4P	0~60M	800	WINCH TYPE	-350	-8,700	
23	Cover Curtain	3.75Kw × 4P	12M	700(Total)	WINCH TYPE	-500	-9,200	
		0.75 × 4P	24M		WINCH TYPE			
24	white Horizont Curtain	3.75Kw × 4P	18M	880(Total)	WINCH TYPE	-250	-9,450	
25	black Horizont Curtain	3.75Kw × 4P	18M	880(Total)	WINCH TYPE	-250	-9,700	
26	Free Single Point Hoist	11Kw × 4P	0~60M	450	WINCH TYPE	-	-	4기
27	Front Side Light Frame	2.2Kw × 4P	12M	400	WINCH TYPE	-	-	2기